

# ADAM-6050 IP I/O Device



- 12 digital inputs; 6 digital outputs
- Supports dry or wet contact
- 10/100 Mbps communication rate
- 24 VDC power input
- · Convenient front panel LED indicators
- Easily installed; surface or DIN rail mounting bracket
- · UL; CE; FCC Class A

## **Performance**

Digital Inputs

**(Sensors):** 12.

Dry Contact: Logic level 0: close to GND. Logic level 1: open. Wet Contact: Logic level 0: 0~3 VDC.

Logic level 1: 10~3 VDC.

Digital Outputs (Relays):

6 (sink type). Open collector to 30 V, 100 mA maximum load.

,

**LAN:** 10/100Base-T (X).

**Protocols:** Modbus/TCP, TCP/IP, UDP and HTTP.

**Watchdog:** System (1.6 second) and Communication

(programmable).

### **Indicators and Connectors**

Indicators: Front panel red and green LEDs for Status/

Speed and Connectivity/Communication.

**Port:** RJ-45 10/100Base-T.

Inputs/Outputs/

**Power:** Plug-in screw terminals.

Data Sheet Number: V260-00

Dated: 3/2016

Vicon data Sheet Number: 8009-7260-00-01 Specifications subject to change without notice.

# **Overview**

The ADAM-6050 IP I/O device fits seamlessly into an existing ViconNet® network to allow external alarm inputs and outputs to any NVR, Workstation or Kollector DVR. The unit provides 12 digital inputs (sensors) and 6 digital outputs (relays). This high-density I/O module has a built-in 10/100 based-T interface for seamless Ethernet connectivity. The unit is compatible with Windows® XP, Vista $^{\text{TM}}$  and 7.0 operating systems and ViconNet 6.6 and higher.

## **Mechanical & Electrical**

**Mounting:** Surface or DIN rail mountable; bracket

included.

**Construction:** ABS and polycarbonate

**Dimensions:** 5.6 in. (142 mm) (H) x 2.6 in. (66 mm) (W)

x 1.2 in. (30 mm) (D).

**Weight:** 0.4 lb (0.2 kg). **Input Power:** 24 VDC (10~30 VDC).

(Customer supplied power supply).

Current: 0.08 A, max.

**Power** 

Consumption: 2 W @ 24 VDC.

Heat Equivalent: 7 btu/hr.

**Power Reversal** 

Protections: Yes.

**Isolation** 

Protection: 2.000 VDC.

#### **Environmental**

Operating

**Temperature:** 14 to 158° F (-10 to 70° C).

**Operating Humidity:** 20 to 95% relative, non-condensing.

**Approvals:** UL, FCC Class A; CE.

Warranty: 3 years.

Vicon, ViconNet and their logos are registered trademarks of Vicon Industries Inc. Copyright © 2016 Vicon Industries Inc. All rights reserved.